

Float Tag Colors

suggested float and wiring box - from Orenco Systems Inc.

B - Blue E - Grey Note: In systems which include floats, Note: Multi-function floats will have this drawing replaces drawing no. "EDW-FA-S-1" more than one marker

Control Panel Series

Float Function Color Code

Splice Box Model

Attention: Failure to follow splicing

instructions will void warranty

* Refer to drawing EIN-SB-SB-1

for splicing instructions.

EDW-FS-S-5

Drawing No.

White Wire

Green Wire

Orenco Systems®

814 AIRWAY AVENUE

SUTHERLIN, OREGON

97479-9012

(541) 459-4449


Suggested pump alarm and control panels from Orenco Systems Inc.



S Series Simplex Control Panels Simplex control panels can be used for pressure sewer (STEP) systems, onsite treatment systems, and pump control into conventional gravity or pressurized drainfields. "S" series pump control panels are a popular choice for a simplex pump and alarm system. These panels include a motor contactor, which increases system life by reducing

the load requirements on the float switches. "S" Series panels also allow options such as a programmable timer or use of larger horsepower

Note: Orenco's A, S, and DAX series of standard electromechanical control panels are specifically designed for use with effluent pumping and onsite treatment systems, when pumping from point "A"



 $-\mathrm{DAX} = \mathrm{duplex}$ alternating control panel

 $^\circ$ All panels require $120~ ext{VAC}$ for the controls


Distributing Valves

Data Sheet

Orenco Systems 1-800-348-9843

Applications

Automatic Distributing Valve Assemblies are used to pressurize multiple zone distribution systems including textile filters, sand filters and drainfields.



Orenco's Automatic Distributing Valve Assemblies are mechanically operated and sequentially redirect the pump's flow to multiple zones or cells in a distribution field. Valve actuation is accomplished by a combination of pressure and flow. Automatic Distributing Valve Assemblies allow the use of smaller horsepower pumps on large sand filters and drainfields. For example, a large community drainfield requiring 300 gpm can use a six-line Valve Assembly to reduce the pump flow rate requirement to only 50 gpm.

Orenco only warrants Automatic Distributing Valves when used in conjunction with High-Head Effluent Pumps with Biotube® Pump Vaults to provide pressure and flow requirements, and to prevent debris from fouling valve operation. An inlet ball valve and a section of clear pipe and union for each outlet are provided for a complete assembly that is easy to maintain and monitor. Ideal valve location is at the high point in the system. Refer to Automatic Distributing Valve Assemblies (NTP-VA-1) for more information.

Standard Models

V4402A, V4403A, V4404A, V4605A, V4606A, V6402A, V6403A, V6404A, V6605A, V6606A. V 64 04A FOR EQUALIZATION TANK TO TREATMENT UNITS Nomenclature

V 66 D5 A FOR NON-RESIDENTIAL ZONES

Indicates assembly Number of active outlets 44 = 4400 series (2-4 outlets)46 = 4600 series (5-6 outlets)64 = 6400 series (2-4 outlets)

Distributing valve

Materials of Construction

Specifications


Unions: Ball Valve: Clear Pipe: V4XXX Distributing Valves: V6XXX Distributing Valves: Sch. 40 PVC per ASTM specification Sch. 80 PVC per ASTM specification Sch. 40 PVC per ASTM specification

Sch. 40 PVC per ASTM specification High-strength noncorrosive ABS polymer and stainless steel High-strength noncorrosive ABS polymer, stainless steel, and die cast metal

NSU-SF-VA-1 Rev. 3.0, © 4/03 Page 1 of 2

Contractor may use any County approved effluent filter, filter specifications provided as a courtesy only Effluent filter specifications from Orenco Systems, Inc.





Biotube™ effluent filter series

Materials of Construction

Vault, pipe coupling, handle components, support coupling and bracket


* Orenco® Biotube® Effluent Filters are covered under multiple U.S. and international patents © 2010 Orenco Systems® Inc.

*Indicates bracket is epoxied to housing (add-on alarm also available)

† Use the slide rail when only one access is available for the filter chamber

‡ Minimum liquid level is measured from the invert of the outlet to the tank floc

8"-15" Diameter Biotube® Effluent Filters (continued)



Specifications

Model	FT0854-36	FT0822-14B	FT1254-36	FT1254-36AR	FT1554
A - Cartridge height, in.	36	14	36	36	36
B - Nominal diameter, in.	8	8	12	12	15
C - Inlet hole height*, in.	22	n/a [†]	22	22	22
D - Vault base to invert height, in.	38	13	38	38	38
E - Vault height	54	22	54	54	54
Number of inlet holes	8	n/a	8	8	8
Inlet hole diameter, in.	1.375	n/a	1.375	1.375	1.
Number of discharge orifices	2	1	1	1	1
Discharge orifice diameter, in.	1.125	1.750	2	2	2
Pipe coupling diameter, in.	4	4	4	4	4
Number of air vents	1	1	1	1	1
Air vent diameter, in.	0.75	1.750	0.75	0.75	0.
Filter surface area [‡] , ft²	14.6	6.0	30.0	30.0	50.
Flow area**, ft²	4.4	1.8	9.0	9.0	15.
* Inlet hole height can vary dependi † No inlet holes required, because in ‡ Filter area is defined as the total s ** Flow area is defined as the total	nfluent enters betw urface area of all ii	veen the vault base an ndividual Biotubes® wi	d the bottom of the f ithin the filter cartrid	ilter cartridge. ge.	,

CORDOBA CENTER 45 MONTEREY ROAD N MARTIN, CA 95046 APN 779-06-002

OMI

1 4-15-2016

COUNTY COMMENTS

. HARTSELL, R.E.H.: P.O. BOX 342 ACIFICA, CA 94044

<u>ح</u>

November 30, 2015

SCALE AS NOTED

BY SRH

9 OF 10

equipment specifications from Geoflow

Solenoid Valves The Solenoid Valve is used to flush field and filters and as zone valves. It is electrically operated.

It is normally closed, and in the event of a power failure the valve will close. Geoflow's automatic water control valves are designed for vertical or horizontal installation. The Wye 'Y' valve body design includes a full bore seat with unobstructed flow path, free of any in-line ribs, supporting cage, or shafts. Its unitized Flexible Super Travel (FST) diaphragm and guid-

ed plug provide a significantly 'look through' passage from end to end resulting in ultra-high flow capacity with minimal pressure loss. The combination of a long travel guided valve plug, peripherally supported diaphragm, and replaceable valve seal provides: ■ No chattering or slamming closed ■ Accurate and stable regulation with smooth motion

■ Low operating pressure requirements

■ No diaphragm erosion and distortion Chemical resistant SVLVB-100 SVLVB 150 SVLVB 200 SVLVB 300 Inlet/Outlet Size (FNPT) 1-5/8" Wye 'Y' Valve pattern 10 - 150 psi 10 - 150 psi 7 - 140 psi 7 - 140 psi Operating range 180 deg F 180 deg F 180 deg F 180 deg F Max pressure Body & cover Nylon reinforced Nylon reinforced Glass filled nylon Metal parts Stainless steel Stainless steel Stainless steel Stainless steel Natural rubber Natural rubber NBR (Buna-N),

Geoflow, Inc. Tel 415-927-6000 / 800-828-3388 Fax 415-927-0120 www.geoflow.com

Glass filled nylo Diaphragm NBR (Buna-N), nylon reinforced nylon reinforced NBR & NR NBR (Buna-N) NBR (Buna-N)

SVLVB200 and

SVLVB 300

Flow Rate vs. Pressure

ALL WASTEFLOW 10 psi 23.10 ft. 34.65 ft. 1.00 gph 20 psi 46.20 ft. 1.16 gph 25 psi 57.75 ft. 30 psi 69.30 ft. 1.44 gph 35 psi 80.85 ft. 40 psi 92.40 ft. 45 psi 103.95

Maximum Length of Run vs. Pressure Flow variation +/- 5% 10 psi 23.10 ft. 170' 15 psi 34.65 ft. 170' 165' 20 psi 46.20 ft. 170' 165' 25 psi 57.75 ft. 170' 165' 30 psi 69.30 ft. 170' 165' 100' 35 psi 80.85 ft. 170' 165' 100' 40 psi 92.40 ft. 170' 165' 100' 45 psi | 103.95 ft. | 170' | 165' | 100'

NOTE: For rolling terrain use Geoflow's WASTEFLOW PC-572 our slow drain anti-siphon dripline

WF16-4-12 WASTEFLOW Classic 12"/1.3gph Alternate flow rates, diameters and spacing available upon WASTEFLOW Classic Specification The dripline shall consist of nominal sized one-half inch linear low density polyethylene tubing, with turbulent flow drip emitters bonded to the inside wall. The drip emitter flow passage shall be 0.053" x 0.053" square. The tubing shall have an outside diameter (O.D.) of approximately .64-inches

Available in 2 standard models WF16-4-24 WASTEFLOW Classic 24"/1.3gph

and an inside diameter (I.D.) of approximately .55-inches. The tubing shall consist of three layers; the inside layer shall be Geoshield® protection, the middle layer shall be black and the outside layer shall be purple striped for easy identification. The dripline shall have emitters regularly spaced 24" (or 12") apart. The turbulent flow emitters shall be molded from virgin polyethylene resin. The turbulent flow emitters shall have nominal discharge rates of 1.16 gallons per hour at 20 psi. The emitters shall be impregnated with Treflan® to inhibit root intrusion for a minimum period of fifteen years and shall be guaranteed by the manufacturer to inhibit root intrusion for this period. WASTEFLOW Classic dripline shall be Geoflow model number WF16-4-24 (or WF16-4-12).

Geoflow, Inc. Tel 415-927-6000 / 800-828-3388 Fax 415-927-0120 www.geoflow.com

The Air Vacuum Breaker bady and ball shall be made of molded plastic. The ball shall be removable for easy cleaning. The Air Vacuum Breaker shall be part number APVBK75m or APVBK100m as supplied by Geoflow,

Air release occurs when air escape the system at startup and

vacuum relief allows air to enter during shutdown. The

in the drip field to keep soil from being sucked into the

emitters due to back siphoning and back pressure. This

is an absolute necessity with underground drip systems.

and any high points of the system.

directing spray downward.

They are also used for proper drainage of the supply and

return manifolds. Use one on the high point of the supply

manifold and one on the high point of the return manifold

Geoflow's new kinetic air vacuum breakers have a twist

off cap that is easy to take apart for cleaning. No need


to remove the valve to maintain it. The large clear

passageway allows lots of air to flow in and out easily.

The protected mushroom cap is ideal for wastewater,

APVBK75m APVBK100m

air vent vacuum breakers are installed at the highest points



Air Vent / Vacuum Relief Valve

Product Sheets-2011 AirVentVacuumRelief(ir) 11E05.indd

Geoflow, Inc. Tel 415-927-6000 / 800-828-3388 Fax 415-927-0120 www.geoflow.com

